

## Pliki .tpl

scripts/basket/address.tpl

```
58                                     <select
59                                     name="phone_country"
60                                     class="select__phone js__phone-country-sele
ct"
- 61                                     autocomplete="chrome-off">
+ 61                                     autocomplete="off"
+ 62                                     aria-label="{translate key='Select country:
%s' s0=''}"
+ 63                                     >
64                                     <option
65                                     value="Poland"
66                                     {if $phone_country == constant('For
m_Shop_Address::PHONE_TYPE_POLAND')}}

113                                     {/if}
114                                     </div>
115                                     {else}
+ 116                                     {assign var="autocomplete" value="" }
+ 117
+ 118                                     {if $str.name|escape == 'mail'}
+ 119                                     {assign var="autocomplete" value="email"}
+ 120                                     {elseif $str.name|escape == 'name'}
+ 121                                     {assign var="autocomplete" value="given-name"}
+ 122                                     {elseif $str.name|escape == 'surname'}
+ 123                                     {assign var="autocomplete" value="family-name"}
+ 124                                     {elseif $str.name|escape == 'phone'}
+ 125                                     {assign var="autocomplete" value="tel"}
+ 126                                     {/if}
+ 127
128                                     <div class="shaded_inputwrap{if $str.error} error{/if} {
if $str.name == 'phone'} js__input-container{/if}" >
129                                     <input
130                                     type="{ $str.type|escape}"

134                                     {if $str.readonly == true} readonly{/if}
```

|       |                                                             |                                                                        |
|-------|-------------------------------------------------------------|------------------------------------------------------------------------|
| 135   |                                                             | {if \$tr.name == 'phone'}                                              |
| 136   |                                                             | data-input-mask-instance="false"                                       |
| - 137 |                                                             | {/if}>                                                                 |
| + 137 |                                                             | {/if}                                                                  |
| + 138 |                                                             | autocomplete="{ \$autocomplete}"                                       |
| + 139 |                                                             | >                                                                      |
| 140   |                                                             | </div>                                                                 |
| 141   |                                                             | {/if}                                                                  |
| 142   |                                                             | </td>                                                                  |
| <hr/> |                                                             |                                                                        |
| 213   |                                                             | </tr>                                                                  |
| 214   |                                                             |                                                                        |
| 215   |                                                             | {foreach from=\$table2 item=tr}                                        |
| + 216 |                                                             | {assign var="autocomplete" value=""}                                   |
| + 217 |                                                             |                                                                        |
| + 218 |                                                             | {if \$tr.name escape == 'coname'}                                      |
| + 219 |                                                             | {assign var="autocomplete" value="organization"}                       |
| + 220 |                                                             | {elseif \$tr.name escape == 'other_address'}                           |
| + 221 |                                                             | {assign var="autocomplete" value="street-address"}                     |
| + 222 |                                                             | {elseif \$tr.name escape == 'zip'}                                     |
| + 223 |                                                             | {assign var="autocomplete" value="postal-code"}                        |
| + 224 |                                                             | {elseif \$tr.name escape == 'city'}                                    |
| + 225 |                                                             | {assign var="autocomplete" value="address-level2"}                     |
| + 226 |                                                             | {elseif \$tr.name escape == 'country'}                                 |
| + 227 |                                                             | {assign var="autocomplete" value="country-name"}                       |
| + 228 |                                                             | {/if}                                                                  |
| + 229 |                                                             |                                                                        |
| 230   |                                                             | <tr class="{ \$tr.name escape}{if \$tr.name == 'vat_eu'} additional-fi |
|       | elds{/if}">                                                 |                                                                        |
| 231   |                                                             | <td class="label">                                                     |
| 232   |                                                             | <label for="input_{ \$tr.name escape}">                                |
| <hr/> |                                                             |                                                                        |
| 244   |                                                             | <select                                                                |
| 245   |                                                             | class="{if \$tr.error} error{/if} {if \$tr.name == 'c                  |
|       | ountry'} js__country-for-phone{/if}"                        |                                                                        |
| 246   |                                                             | name="{ \$tr.name escape}"                                             |
| - 247 |                                                             | id="input_{ \$tr.name escape}">                                        |
| + 247 |                                                             | id="input_{ \$tr.name escape}"                                         |
| + 248 |                                                             | autocomplete="{ \$autocomplete}"                                       |
| + 249 |                                                             | >                                                                      |
| 250   |                                                             | {foreach from=\$tr.list item=c key=k}                                  |
| 251   |                                                             | <option value="{ \$k escape}" {if \$k == \$tr.value}                   |
|       | selected="selected" {/if} {if \$tr.html5data                |                                                                        |
| 252   |                                                             | {foreach from=\$tr.html5data key=html5k ite                            |
|       | m=html5d data-{ \$html5k}="{ \$html5d.\$k}" {/foreach} {/if |                                                                        |
| <hr/> |                                                             |                                                                        |
| 286   |                                                             | {/if}                                                                  |
| 287   |                                                             | {else}                                                                 |

```

288                                     <div class="shaded_inputwrap{if $tr.error} error{/if}">
- 289                                     <input {if $tr.name == 'zip'}data-mask="__-__" dat
a-pattern="{literal}^\(\\d{2})\\(-)\\(\\d{3})${/literal}" data-valid-pattern="00-000"/>{/if} type="{if $tr.name == 'zip'}tel{else}{ $tr.type|escap
e}/{/if}" name="{ $tr.name|escape}" value="{ $tr.value|escape}"id="input_{ $tr.name|escape}">
+ 289                                     <input
+ 290                                     {if $tr.name == 'zip'}
+ 291                                     data-mask="__-__"
+ 292                                     data-pattern="{literal}^\(\\d{2})\\(-)\\(\\d{3})$ {
/literal}"
+ 293                                     data-valid-pattern="00-000"
+ 294                                     {/if}
+ 295                                     type="{if $tr.name == 'zip'}tel{else}{ $tr.type|
escape}/{/if}"
+ 296                                     name="{ $tr.name|escape}"
+ 297                                     value="{ $tr.value|escape}"
+ 298                                     id="input_{ $tr.name|escape}"
+ 299                                     autocomplete="{ $autocomplete}"
+ 300                                     >
301                                     </div>
302                                     {/if}
303                                 </td>

```

```

369                                     {/if}
370
371                                     {foreach from=$table3 item=tr}
+ 372                                     {assign var="autocomplete" value="" }
+ 373
+ 374                                     {if $tr.name|escape == 'name2'}
+ 375                                     {assign var="autocomplete" value="given-name"}
+ 376                                     {elseif $tr.name|escape == 'surname2'}
+ 377                                     {assign var="autocomplete" value="family-name"}
+ 378                                     {elseif $tr.name|escape == 'phone2'}
+ 379                                     {assign var="autocomplete" value="tel"}
+ 380                                     {elseif $tr.name|escape == 'coname2'}
+ 381                                     {assign var="autocomplete" value="organization"}
+ 382                                     {elseif $tr.name|escape == 'other_address2'}
+ 383                                     {assign var="autocomplete" value="street-address"}
+ 384                                     {elseif $tr.name|escape == 'zip2'}
+ 385                                     {assign var="autocomplete" value="postal-code"}
+ 386                                     {elseif $tr.name|escape == 'city2'}
+ 387                                     {assign var="autocomplete" value="address-level2"}
+ 388                                     {elseif $tr.name|escape == 'country2'}
+ 389                                     {assign var="autocomplete" value="country-name"}
+ 390                                     {/if}
+ 391
392                                     <tr class="different { $tr.name|escape} {if $tr.name == 'phone2'}js_
_phone-table-row{/if}">
393                                     <td class="label">
394                                     <label for="input_{ $tr.name|escape}">

```

|       |                                        |                                             |
|-------|----------------------------------------|---------------------------------------------|
| 406   |                                        | <select                                     |
| 407   |                                        | name="phone_country2"                       |
| 408   |                                        | class="select__phone js__phone-country-sele |
|       | ct"                                    |                                             |
| - 409 |                                        | autocomplete="chrome-off">                  |
| + 409 |                                        | autocomplete="off"                          |
| + 410 |                                        | aria-label="{translate key='Select country: |
|       | %s' s0=' '}"                           |                                             |
| + 411 |                                        | autocomplete="{autocomplete}"               |
| + 412 |                                        | >                                           |
| 413   |                                        | <option                                     |
| 414   |                                        | value="Poland"                              |
| 415   |                                        | {if \$phone_country2 == constant('Fo        |
|       | rm_Shop_Address::PHONE_TYPE_POLAND')}} |                                             |

|       |                                                                 |                                                       |
|-------|-----------------------------------------------------------------|-------------------------------------------------------|
| 443   |                                                                 | <select                                               |
| 444   |                                                                 | class="{if \$tr.error} error{/if} {if \$tr.name == 'c |
|       | ountry2'} js__country-for-phone2{/if}"                          |                                                       |
| 445   |                                                                 | name="{ \$tr.name escape}"                            |
| - 446 |                                                                 | id="input_{ \$tr.name escape}">                       |
| + 446 |                                                                 | id="input_{ \$tr.name escape}"                        |
| + 447 |                                                                 | autocomplete="{autocomplete}"                         |
| + 448 |                                                                 | >                                                     |
| 449   |                                                                 | {foreach from=\$tr.list item=c key=k}                 |
| 450   |                                                                 | <option value="{ \$k escape}" {if \$k == \$tr.va      |
|       | lue} selected="selected" {/if} {if \$tr.html5data               |                                                       |
| 451   |                                                                 | }{foreach from=\$tr.html5data key=html5k              |
|       | item=html5d} data-{ \$html5k}="{ \$html5d.\$k}" {/foreach} {/if |                                                       |

|       |                |                                                    |
|-------|----------------|----------------------------------------------------|
| 466   |                | type="{if \$tr.name == 'zip2'}tel{else}{ \$tr.type |
|       | escape} {/if}" |                                                    |
| 467   |                | name="{ \$tr.name escape}"                         |
| 468   |                | value="{ \$tr.value escape}"                       |
| - 469 |                | id="input_{ \$tr.name escape}">                    |
| + 469 |                | id="input_{ \$tr.name escape}"                     |
| + 470 |                | autocomplete="{autocomplete}"                      |
| + 471 |                | >                                                  |
| 472   |                | </div>                                             |
| 473   |                | {/if}                                              |
| 474   |                | </td>                                              |

## scripts/body\_head.tpl

|      |                                                                                                                 |
|------|-----------------------------------------------------------------------------------------------------------------|
| 70   | {if 1 == \$skin_settings->header->basket}                                                                       |
| 71   | {dynamic}                                                                                                       |
| 72   | <div class="basket right{if 0 == \$user->basket->countProducts()} empty-basket{/if}">                           |
| - 73 | <a href="{route key='basket'}" title="{translate key='Cart'}" class="count" aria-label="{translate key='Go to c |

```

+ 73         art'}">
+ 74         href="{route key='basket'}"
+ 75         title="{translate key='Cart'}"
+ 76         class="count"
+ 77         aria-label="{translate key='Products in cart %d.' s0=$user->basket->countProducts()} {translate key='Go to
cart'}"
+ 78     >
79         
80         <span class="countlabel">
81             <span>{translate key="Cart"}:</span>

```

## scripts/headerlinks.tpl

```

15         {if $link->getHref() || $link->isActiveCategory() || $link->isActiveNewsCategory()}
16             <li{if $link->hasSubCategories() || $link->hasNewsSubCategories()} class="parent"{/if}{if $link->isCategory
    ()} id="hcategory_{$link->getCategoryId()}|escape}" {elseif $link->isNewsCategory()} id="ncategory_{$link->getNewsCategoryId()}|escape}" {/i
f}>
17                 <h3>
- 18                 <a {if $link->isPopup()}target="_blank" rel="noopener"{/if} href="{ $link->getHref($view)|escape}" t
    title="{ $link->getTitle()}|escape}" id="headlink{$link->getIdentifier()}" class="spanhover mainlevel">
+ 18                 <a {if $link->isPopup()}target="_blank" rel="noopener" aria-label="{translate key="%s - opens in a
    new tab" s1=$link->getTitle()}|escape}" {/if} href="{ $link->getHref($view)|escape}" title="{ $link->getTitle()}|escape}" id="headlink{$link-
>getIdentifier()}" class="spanhover mainlevel">
19                     <span>{ $link->getTitle()}|escape}</span>
20                     
21                 </a>

```

## scripts/panel/address.tpl

```

80             {/if}
81
82             <div class="links">
- 83                 <a href="{route key='panelAddressEdit' addressId=$address->address_book_id}" class="edi
    t btn spanhover">
+ 83                 <a href="{route key='panelAddressEdit' addressId=$address->address_book_id}" class="edi
    t btn spanhover" aria-label="{translate key='Edit address %s, %s %s' s1=$address->street_1|escape s2=$address->zip_code|escape s3=$addre
ss->city|escape}">
84                     
85                     <span>{translate key='edit'}</span>
86                 </a>
87
- 88                 <a href="{route key='panelAddressRemove' addressId=$address->address_book_id}" class="r
    emove btn spanhover titlequestion" title="{translate key='Are you sure you want to remove the address: %s, %s %s?' p1=$address->street_1
    |escape p2=$address->zip_code|escape p3=$address->city|escape}">
+ 88                 <a href="{route key='panelAddressRemove' addressId=$address->address_book_id}" class="r
    emove btn spanhover titlequestion" title="{translate key='Are you sure you want to remove the address: %s, %s %s?' p1=$address->street_1
    |escape p2=$address->zip_code|escape p3=$address->city|escape}" aria-label="{translate key='Remove address %s, %s %s' s1=$address->stree
t_1|escape s2=$address->zip_code|escape s3=$address->city|escape}">
89                     

```

```

90         <span>{translate key='remove'}</span>
91     </a>
92
93     {if 0 == $address->default}
- 94         <a href="{route key='panelAddressDefault' addressId=$address->address_book_id}" cla
ss="default spanhover btn">
+ 94         <a href="{route key='panelAddressDefault' addressId=$address->address_book_id}" cla
ss="default spanhover btn" aria-label="{translate key='Set default billing address %s, %s %s' s1=$address->street_1|escape s2=$address->
zip_code|escape s3=$address->city|escape}">
95             
96             <span>{translate key='set as billing address'}</span>
97         </a>

```

```

103     {/if}
104
105     {if 0 == $address->shipping_default}
- 106         <a href="{route key='panelAddressShipping' addressId=$address->address_book_id}" cl
ass="shipping spanhover btn">
+ 106         <a href="{route key='panelAddressShipping' addressId=$address->address_book_id}" cl
ass="shipping spanhover btn" aria-label="{translate key='Set default delivery address %s, %s %s' s1=$address->street_1|escape s2=$addres
s->zip_code|escape s3=$address->city|escape}">
107             
108             <span>{translate key='set as delivery address'}</span>
109         </a>

```

## scripts/panel/favourites.tpl

```

29         <table class="favourites classic table">
30             <thead>
31                 <tr>
- 32                     <td class="name">{translate key='Name'}</td>
- 33                     <td class="price">{translate key='Price'}</td>
+ 32                     <th class="name">{translate key='Name'}</th>
+ 33                     <th class="price">{translate key='Price'}</th>
34                 {if 1 == $skin_settings->productdetails->availability}
- 35                     <td class="sum">{translate key='Availability status'}</td>
+ 34                     <th class="sum">{translate key='Availability status'}</th>
35                 {/if}
- 36                     <td class="actions">{translate key='Actions'}</td>
+ 36                     <th class="actions">{translate key='Actions'}</th>
37                 </tr>
38             </thead>
39         </table>

```

## scripts/panel/index.tpl

```

29         <table class="orders payable table">
30             <thead>
31                 <tr>

```

```
- 32 <td class="id">{translate key='Order no.'}</td>
- 33 <td class="sum">{translate key='Value'}</td>
- 34 <td class="status">{translate key='Status'}</td>
- 35 <td class="parcels">{translate key='Shipment'}</td>
+ 32 <th class="id">{translate key='Order no.'}</th>
+ 33 <th class="sum">{translate key='Value'}</th>
+ 34 <th class="status">{translate key='Status'}</th>
+ 35 <th class="parcels">{translate key='Shipment'}</th>
36 </tr>
37 </thead>
38 <tbody>
```

```
175 {/if}
176
177 {if $loyalty_exchange_enabled}
- 178 <a href="{route key='loyaltyList'}" class="loyaltylist button spanhover">
- 179 
- 180 <span>{translate key='Go to the list of products that you can exchange for points'}</span>
- 181 </a>
+ 178 <li>
+ 179 <a href="{route key='loyaltyList'}" class="loyaltylist button spanhover">
+ 180 
+ 181 <span>{translate key='Go to the list of products that you can exchange for points'}</span>
an>
+ 182 </a>
+ 183 </li>
184 {/if}
185 </ul>
186 {/if}
```

```
190 <table class="orders exchanged classic table">
191 <thead>
192 <tr>
- 193 <td class="prod">{translate key='Product'}</td>
- 194 <td class="quantity">{translate key='Quantity'}</td>
- 195 <td class="points">{translate key='Points'}</td>
+ 193 <th class="prod">{translate key='Product'}</th>
+ 194 <th class="quantity">{translate key='Quantity'}</th>
+ 195 <th class="points">{translate key='Points'}</th>
196 </tr>
197 </thead>
198 <tbody>
```

## scripts/panel/orders.tpl

```
26 <table class="orders classic table">
27 <thead>
28 <tr>
```

```

- 29         <td class="id">{translate key='ID'}</td>
- 30     <td class="date rwd-hide-medium">{translate key='Order date'}</td>
- 31     <td class="sum">{translate key='Value'}</td>
- 32     <td class="shipping">{translate key='Shipping method'}</td>
- 33     {if $config_confirm}<td class="status">{translate key='Confirmation'}</td>{if}
- 34     <td class="actions">{translate key='Actions'}</td>
+ 29     <th class="id">{translate key='ID'}</th>
+ 30     <th class="date rwd-hide-medium">{translate key='Order date'}</th>
+ 31     <th class="sum">{translate key='Value'}</th>
+ 32     <th class="shipping">{translate key='Shipping method'}</th>
+ 33     {if $config_confirm}<th class="status">{translate key='Confirmation'}</th>{if}
+ 34     <th class="actions">{translate key='Actions'}</th>
35         </tr>
36     </thead>
37

```

```

57         {/if}
58
59         <td class="actions">
- 60             <a href="{route key='panelOrder' orderId=$id}" class="details btn btn-red spanhover" ti
tle="{translate key='Order details'}">
+ 60             <a href="{route key='panelOrder' orderId=$id}" class="details btn btn-red spanhover" ti
tle="{translate key='Order details'}" aria-label="{translate key='Order details'} {$id|escape}">
61                 
62                 <span>{translate key='details'}</span>
63             </a>

```

```

73         {/if}
74
75         {if $order->invoice && true == $show_invoice}
- 76             <a href="{baseDir}/console/invoices/pdf/id/{$order->invoice->invoice->invoice_id}"
class="invoice btn spanhover">
+ 76             <a href="{baseDir}/console/invoices/pdf/id/{$order->invoice->invoice->invoice_id}"
class="invoice btn spanhover" aria-label="{translate key='Invoice for order'} {$id|escape}">
77                 
78                 <span>{translate key='invoice'}</span>
79             </a>

```

## Pliki .css

## Pliki .less

### styles/\_basket.less

```

159         max-width: 75%;

```



```
160
161         label {
- 162         display: inline;
+ 162         display: inline;
163     }
164 }
165
```

---

```
266     margin-top: 1em;
267     clear: both;
268     overflow: hidden;
+ 269     padding: 1px 4px;
270
271     .forward {
272         float: right;
```

---

```
354     clear: both;
355     overflow: hidden;
356     margin-top: 1em;
+ 357     padding: 4px;
358
359     .important {
360         float: right;
```

---

## styles/\_customer\_privacy.less

```
49
50     &__advanced-content {
51         overflow: auto;
+ 52         padding-left: 3px;
53     }
54
55     &__content {
```

---

## styles/\_formBasic.less

```
296     }
297
298     &:focus-visible + label {
- 299         outline: 2px solid @maincolor;
- 300         outline-offset: 2px;
+ 299         &::after {
+ 300             outline: 2px solid @maincolor;
+ 301             outline-offset: 6px;
+ 302         }
303     }
304 }
```

---

## styles/\_menu.less

```

38         &:hover {
39             text-decoration: underline;
40         }
+ 41
+ 42         &:focus-visible {
+ 43             outline-offset: -2px;
+ 44         }
45     }
46 }
47

```

## styles/\_modal.less

```

104 .modal-footer {
105     margin-bottom: 2em;
106     overflow: hidden;
+ 107     padding: 4px 0;
108
109     a {
110         text-transform: uppercase;

```

## styles/\_modules.less

```

953     }
954 }
955 }
+ 956
+ 957 .loyaltylist {
+ 958     text-decoration: underline;
+ 959 }
960 }
961
962 #box_loyalty {

```

## styles/\_panel.less

```

50
51 .favourites {
52     thead {
- 53         td {
+ 53         td,
+ 54         th {
55             background-color: @maincolor;
56             color: @colorWhite;

```

## styles/\_tableBasic.less

```
12         border-spacing: 0;
13
14     thead {
15 -   td {
16 +   td,
17 +   th {
18         padding: 0.6em 0.7em;
19         background-color: transparent;
20         color: inherit;
```

```
37     }
38 }
39
40 -   td {
41 +   td, th {
42         padding: 5px 8px;
43         line-height: 20px;
44         text-align: left;
```

## Pliki .js