

Pliki .tpl

scripts/contact/_form.tpl

```
16         </div>
17
18         <div class="f-grid-9">
- 19             <input id="contact1" type="text" name="name" value="{ $data.name|escape}" size="30" class="{if $data_error.name}
error{/if}" autocomplete="name" >
+ 19             <input id="contact1" type="text" name="name" value="{ $data.name|escape}" size="30" class="{if $data_error.name}
error{/if}" {if $data_error.name}aria-invalid="true" aria-describedby="error_name"{/if} autocomplete="name">
20                 {if $data_error.name}
- 21                 <ul class="row error">
+ 21                 <ul class="row error" id="error_name">
22                     {foreach from=$data_error.name item=err_text}
23                     <li>{$err_text|escape}</li>
24                     {/foreach}

33         </div>
34
35         <div class="f-grid-9">
- 36             <input id="contact2" type="email" name="mail" value="{ $data.mail|escape}" size="30" class="{if $data_error.mail}
error{/if}" autocomplete="email">
+ 36             <input id="contact2" type="email" name="mail" value="{ $data.mail|escape}" size="30" class="{if $data_error.mail}
error{/if}" {if $data_error.mail}aria-invalid="true" aria-describedby="error_mail"{/if} aria-required="true" autocomplete="email">
37                 {if $data_error.mail}
- 38                 <ul class="error">
+ 38                 <ul class="error" id="error_mail">
39                     {foreach from=$data_error.mail item=err_text}
40                     <li>{$err_text|escape}</li>
41                     {/foreach}

50         </div>
51
52         <div class="f-grid-9">
- 53             <input id="contact3" type="text" name="subject" value="{ $data.subject|escape}" size="30" class="{if $data_error
.subject}error{/if}">
+ 53             <input id="contact3" type="text" name="subject" value="{ $data.subject|escape}" size="30" class="{if $data_error
.subject}error{/if}" {if $data_error.subject}aria-invalid="true" aria-describedby="error_subject"{/if}>
```

```

54         {if $data_error.subject}
- 55         <ul class="error">
+ 55         <ul class="error" id="error_subject">
56             {foreach from=$data_error.subject item=err_text}
57                 <li>{$err_text|escape}</li>
58             {/foreach}

67     </div>
68
69     <div class="f-grid-9">
- 70         <textarea rows="5" cols="30" id="contact4" name="text" class="{if $data_error.text}error{/if}">{$data.text|esca
pe}</textarea>
+ 70         <textarea rows="5" cols="30" id="contact4" name="text" class="{if $data_error.text}error{/if}" {if $data_error.
text}aria-invalid="true" aria-describedby="error_text"{/if} aria-required="true">{$data.text|escape}</textarea>
71         {if $data_error.text}
- 72         <ul class="error">
+ 72         <ul class="error" id="error_text">
73             {foreach from=$data_error.text item=err_text}
74                 <li>{$err_text|escape}</li>
75             {/foreach}

91     {/if}
92
93     {if $field->field->type == constant('Logic_AdditionalField::TYPE_HIDDEN')}
- 94     {additionalField field=$field name=$name value=$additional_value.$name|escape}
+ 94     {additionalField field=$field name=$name value=$additional_value.$name|escape error=$data_error.$name}
95     {elseif $field->field->type == constant('Logic_AdditionalField::TYPE_INFO')}
96     <div class="input_info">
97         {$field->translation->description}

119         <div class="label-checkbox">
120         {/if}
121         {if $field->field->type == constant('Logic_AdditionalField::TYPE_CHECKBOX')}
- 122         {additionalField field=$field name=$name value=$data.$name editable=true}
+ 122         {additionalField field=$field name=$name value=$data.$name editable=true error=$data_error.$name}
123         <label for="{ $name|escape}">{$field->translation->description}</label>
124         {elseif $field->field->type == constant('Logic_AdditionalField::TYPE_SELECT')}
- 125         {additionalField field=$field name=$name value=$additional_value.$name|escape editable=true}
+ 125         {additionalField field=$field name=$name value=$additional_value.$name|escape editable=true error=$
data_error.$name}
126         {else}
127         <div class="{if $data_error.$name}error{/if}" class="f-grid-7">
- 128         {additionalField field=$field name=$name value=$data.$name|escape editable=true size=30}
+ 128         {additionalField field=$field name=$name value=$data.$name|escape editable=true size=30 error=$
data_error.$name}
129         </div>
130         {/if}
131     </div>

```

```

135         {if $data_error.$name}
136         <div class="row">
137             <div class="error">
- 138                 {formErrors errors=$data_error.$name class="input_error"}
+ 138                 {formErrors errors=$data_error.$name class="input_error" name=$name}
139             </div>
140         </div>
141     {/if}

```

scripts/footer.tpl

```

41 <div class="modal-overlay"></div><!-- overlay for modal lightbox-->
42
43 {feature name="aria_live_rwd"}
- 44     <div id="aria-live-assertive" role="region" aria-live="assertive" aria-atomic="true" class="sr-only" tabindex="-1"></div>
+ 44     <div
+ 45         id="aria-live-assertive"
+ 46         role="log"
+ 47         aria-live="assertive"
+ 48         aria-atomic="true"
+ 49         class="sr-only"
+ 50         tabindex="-1"
+ 51     ></div>
52 {/feature}

```

scripts/login/register.tpl

```

57         {/if}
58
59         <span class="checkbox-wrap">
- 60             <input type="{ $tr.type|escape}" name="{ $tr.name|escape}" value="1" id="input_{$
tr.name|escape}" {if $tr.value} checked{/if}>
+ 60             <input
+ 61                 type="{ $tr.type|escape}"
+ 62                 name="{ $tr.name|escape}"
+ 63                 value="1"
+ 64                 id="input_{$tr.name|escape}"
+ 65                 {if $tr.value} checked{/if}
+ 66                 {if true == $tr.obligatory} aria-required="true" {/if}
+ 67                 {if $tr.error}
+ 68                     aria-invalid="true"
+ 69                     aria-describedby="error_{$tr.name|escape}"
+ 70                 {/if}
+ 71             >
72             <label for="input_{$tr.name|escape}"></label>
73         </span>
74

```

```

83         </div>
84     {else}
85         <span class="shaded_inputwrap{if $tr.error} error{/if}">
- 86             <input type="{ $tr.type|escape}" name="{ $tr.name|escape}" value="{ $tr.value|escape}" size="25" id="input_{ $tr.name|escape}" {if $tr.readonly == true} readonly{/if} {if $tr.hint }aria-describedby="hint_{ $tr.name|escape}"{/if}>
+ 86             <input
+ 87                 type="{ $tr.type|escape}"
+ 88                 name="{ $tr.name|escape}"
+ 89                 value="{ $tr.value|escape}"
+ 90                 size="25"
+ 91                 id="input_{ $tr.name|escape}"
+ 92                 {if $tr.readonly == true} readonly{/if}
+ 93                 {if true == $tr.obligatory} aria-required="true"/>{/if}
+ 94                 {if $tr.error}aria-invalid="true"/>{/if}
+ 95                 {if $tr.hint or $tr.error}aria-describedby="{if $tr.hint }hint_{ $tr.name|escape} {/if}{if $tr.error}error_{ $tr.name|escape}/{/if}"{/if}
+ 96             >
97         </span>
98     {/if}
99
100     {if $tr.error}
101         <div>
- 102             <ul class="input_error">
+ 92             <ul class="input_error" id="error_{ $tr.name|escape}">
93                 {foreach from=$tr.error item=err_text}
94                     <li>{ $err_text|escape}</li>
95                 {/foreach}

```

```

148
149     <div class="input">
150         {if 'select' == $tr.type}
- 151             <select class="{if $tr.error} error{/if}" name="{ $tr.name|escape}" id="input_{ $tr.name|escape}">
+ 151             <select
+ 152                 class="{if $tr.error} error{/if}"
+ 153                 name="{ $tr.name|escape}"
+ 154                 id="input_{ $tr.name|escape}"
+ 155                 {if true == $tr.obligatory} aria-required="true"/>{/if}
+ 156                 {if $tr.error}
+ 157                     aria-invalid="true"
+ 158                     aria-describedby="error_{ $tr.name|escape}"
+ 159                 {/if}
+ 160             >
161             {foreach from=$countries_logiclist item=c}
162                 <option data-value="{ $c->getIdentifier()}" data-region="{if $c->country
->regions}1{else}0{/if}" {if $c->country->isocode == $tr.value} selected="selected"/>{/if} value="{ $c->country->isocode|escape}">
163                 { $c->getLocalizedName()}

```

```

166         </select>
167     {else}
168         <span class="shaded_inputwrap{if $str.error} error{/if}">
- 169             <input {if $str.name == 'zip'}data-mask="__-__" data-pattern="{literal}^\(\\d
+ 169             <input
+ 170                 {if $str.name == 'zip'}data-mask="__-__" data-pattern="{literal}^\(\\d{2}
+ 171                 type="{ $str.type|escape}"
+ 172                 name="{ $str.name|escape}"
+ 173                 value="{ $str.value|escape}"
+ 174                 size="25"
+ 175                 id="input_{ $str.name|escape}"
+ 176                 {if true == $str.obligatory} aria-required="true"/>{/if}
+ 177                 {if $str.error}aria-invalid="true"/>{/if}
+ 178                 {if $str.hint or $str.error}aria-describedby="{if $str.hint }hint_{ $str.nam
+ 179                 >
180             </span>
181         {/if}
182
183         {if $str.error}
184             <div>
- 185                 <ul class="input_error">
+ 175                 <ul class="input_error" id="error_{ $str.name|escape}">
176                     {foreach from=$str.error item=err_text}
177                         <li>{ $err_text|escape}</li>
178                     {/foreach}

```

```

216         {/if}
217
218         {if $field->field->type == constant('Logic_AdditionalField::TYPE_HIDDEN')}
- 219             {additionalField field=$field name=$name value=$additional_value.$name|escape}
+ 219             {additionalField field=$field name=$name value=$additional_value.$name|escape error
+ 220             =$additional_error.$name}
221         {elseif $field->field->type == constant('Logic_AdditionalField::TYPE_INFO')}
222             <div class="input_info">
                { $field->translation->description}

```

```

235         </span>
236         {if $field->field->type == constant('Logic_AdditionalField::TYPE_CHECKBOX')}
237             <span class="checkbox-wrap">
- 238                 {additionalField field=$field name=$name value=$additional_value.$name editab
+ 238                 {additionalField field=$field name=$name value=$additional_value.$name editab
                le=true}
- 238                 {additionalField field=$field name=$name value=$additional_value.$name editab
+ 238                 {additionalField field=$field name=$name value=$additional_value.$name editab
                le=true error=$additional_error.$name}

```

```

239         <label for="{ $name|escape}"></label>
240     </span>
241     <label for="{ $name|escape}">{ $field->translation->description}</label>
242     {elseif $field->field->type == constant('Logic_AdditionalField::TYPE_SELECT')}
- 243     {additionalField field=$field name=$name value=$additional_value.$name|escape edi
table=true}
+ 243     {additionalField field=$field name=$name value=$additional_value.$name|escape edi
table=true error=$additional_error.$name}
244     {else}
245     <span class="shaded_inputwrap{if $additional_error.$name} error{/if}">
- 246     {additionalField field=$field name=$name value=$additional_value.$name|escape ed
itable=true size=25}
+ 246     {additionalField field=$field name=$name value=$additional_value.$name|escape ed
itable=true size=25 error=$additional_error.$name}
247     </span>
248     {/if}
249 </div>

```

```

252
253     {if $additional_error.$name}
254     <div class="error">
- 255     {formErrors errors=$additional_error.$name class="input_error"}
+ 255     {formErrors errors=$additional_error.$name class="input_error" name=$name}
256     </div>
257     {/if}
258 {/foreach}

```

```

265     <em class="color">{if true == $tr.obligatory}*{else}&nbsp;&nbsp; {/if}</em>
266
267     <span class="checkbox-wrap">
- 268     <input type="{ $tr.type|escape}" name="{ $tr.name|escape}" value="1" id="input_{$
tr.name|escape}"{if $tr.value} checked{/if}>
+ 268     <input
+ 269     type="{ $tr.type|escape}"
+ 270     name="{ $tr.name|escape}"
+ 271     value="1"
+ 272     id="input_{$tr.name|escape}"
+ 273     {if $tr.value} checked{/if}
+ 274     {if true == $tr.obligatory} aria-required="true"/>
+ 275     {if $tr.error}
+ 276     aria-invalid="true"
+ 277     aria-describedby="error_{$tr.name|escape}"
+ 278     {/if}
+ 279     >
280     <label for="input_{$tr.name|escape}"></label>
281 </span>
282

```

```

295                                     </span>
296
297                                     <span class="shaded_inputwrap{if $tr.error} error{/if}">
- 298                                     <input type="{ $tr.type|escape}" name="{ $tr.name|escape}" value="{ $tr.value|esca
pe}" size="25" id="input_{ $tr.name|escape}" />
+ 298                                     <input
+ 299                                     type="{ $tr.type|escape}"
+ 300                                     name="{ $tr.name|escape}"
+ 301                                     value="{ $tr.value|escape}"
+ 302                                     size="25"
+ 303                                     id="input_{ $tr.name|escape}"
+ 304                                     {if true == $tr.obligatory} aria-required="true"{/if}
+ 305                                     {if $tr.error}
+ 306                                     aria-invalid="true"
+ 307                                     aria-describedby="error_{ $tr.name|escape}"
+ 308                                     {/if}
+ 309                                     />
310                                     </span>
311                                 {/if}
312
313                                 {if $tr.error}
314                                 <div>
- 315                                 <ul class="input_error">
+ 304                                 <ul class="input_error" id="error_{ $tr.name|escape}">
305                                     {foreach from=$tr.error item=err_text}
306                                     <li>{ $err_text|escape}</li>
307                                     {/foreach}

```

scripts/panel/address-edit.tpl

```

37                                     <table class="address-handler">
38                                     <tbody>
39                                     {foreach from=$table item=tr}
+ 40                                     {assign var="autocomplete" value="" }
+ 41
+ 42                                     {if $tr.name|escape == 'name'}
+ 43                                     {assign var="autocomplete" value="given-name"}
+ 44                                     {elseif $tr.name|escape == 'surname'}
+ 45                                     {assign var="autocomplete" value="family-name"}
+ 46                                     {elseif $tr.name|escape == 'phone'}
+ 47                                     {assign var="autocomplete" value="tel"}
+ 48                                     {elseif $tr.name|escape == 'coname'}
+ 49                                     {assign var="autocomplete" value="organization"}
+ 50                                     {elseif $tr.name|escape == 'other_address'}
+ 51                                     {assign var="autocomplete" value="street-address"}
+ 52                                     {elseif $tr.name|escape == 'zip'}
+ 53                                     {assign var="autocomplete" value="postal-code"}
+ 54                                     {elseif $tr.name|escape == 'city'}
+ 55                                     {assign var="autocomplete" value="address-level2"}
+ 56                                     {elseif $tr.name|escape == 'country'}

```

```

+ 57 {assign var="autocomplete" value="country-name"}
+ 58 {/if}
+ 59
60
61 <tr>
62     <td class="label">
        <label for="input_{$str.name|escape}">

70
71     <td class="input">
72         {if 'select' == $str.type}
- 73         <select class="{if $str.error} error{/if}" name="{ $str.name|escape}" id="input_{$str.name|escape}">
+ 73         <select class="{if $str.error} error{/if}" name="{ $str.name|escape}" id="input_{$str.name|escape}" autocomplete="{ $autocomplete}">
74             {foreach from=$countries_logiclist item=c}
75                 <option data-value="{ $c->getIdentifier()}" {if $c->country->isocode == $str.value} selected="selected" {/if} data-region="{if $c->country->regions}1{else}0{/if}" value="{ $c->country->isocode|escape}">
76                     { $c->getLocalizedName()}

79             </select>
80         {else}
81             <div class="shaded_inputwrap{if $str.error} error{/if}">
- 82                 <input {if $str.name == 'zip'}data-mask="__-__" data-pattern="{literal}^(\d{2})(-)(\d{3})$/literal}" data-valid-pattern="00-000" {/if} type="{ $str.type|escape}" name="{ $str.name|escape}" value="{ $str.value|escape}" size="25" id="input_{$str.name|escape}">
+ 82                 <input
+ 83                     {if $str.name == 'zip'}data-mask="__-__" data-pattern="{literal}^(\d{2})(-)(\d{3})$/literal}" data-valid-pattern="00-000" {/if}
+ 84                     type="{ $str.type|escape}" name="{ $str.name|escape}" value="{ $str.value|escape}" size="25" id="input_{$str.name|escape}" autocomplete="{ $autocomplete}"
+ 85                     {if true == $str.obligatory} aria-required="true" {/if} {if $str.error} aria-invalid="true" {/if}
+ 86                     {if $str.hint or $str.error} aria-describedby="{if $str.hint }hint_{$str.name|escape} {/if}{if $str.error}error_{$str.name|escape}{/if}" {/if}>
87                 </div>
88             {/if}
89         </td>
90
91         {if $str.rowspan > 0}
- 92         <td class="{if $str.hint}hint{/if}" {if $str.rowspan > 1} rowspan="{ $str.rowspan|escape}" {/if}>
+ 92         <td class="{if $str.hint}hint{/if}" {if $str.rowspan > 1} rowspan="{ $str.rowspan|escape}" {/if} id="hint_{$str.name|escape}">
89             { $str.hint|escape|nl2br}
90         </td>
91     {/if}

99 <tr>
100     <td />

```



```

101         <td class="error">
- 102         <ul class="input_error">
+ 102         <ul class="input_error" id="error_{$str.name|escape}">
103             {foreach from=$str.error item=err_text}
104                 <li>{$err_text|escape}</li>
105             {/foreach}

```

scripts/panel/edit.tpl

```

30         <em class="color">*</em> {translate key="E-mail"}:
31     </label>
32     <div class="shaded_inputwrap">
- 33         <input type="text" name="mail" id="mail_input" value="{$data.mail|escape}" size="30" class="{if
    $data_error.surname} error{/if}">
+ 33         <input type="text" name="mail" id="mail_input" value="{$data.mail|escape}" size="30" class="{if
    $data_error.mail} error{/if}" {if $data_error.mail}aria-invalid="true" aria-describedby="error_mail"{/if} aria-required="true" autocomp
    lete="email">
34     </div>
35     {if $data_error.mail}
- 36         <ul class="input_error">
+ 36         <ul class="input_error error" id="error_mail">
37             {foreach from=$data_error.mail item=err_text}
38                 <li>{$err_text|escape}</li>
39             {/foreach}

```

```

42
43     <label for="name_input">{translate key="First name"}:</label>
44     <div class="shaded_inputwrap">
- 45         <input type="text" name="name" id="name_input" value="{$data.name|escape}" size="30" class="{if
    $data_error.surname} error{/if}">
+ 45         <input type="text" name="name" id="name_input" value="{$data.name|escape}" size="30" class="{if
    $data_error.name} error{/if}" {if $data_error.name}aria-invalid="true" aria-describedby="error_name"{/if} autocomplete="given-name">
46     </div>
47     {if $data_error.name}
- 48         <ul class="input_error">
+ 48         <ul class="input_error error" id="error_name">
49             {foreach from=$data_error.name item=err_text}
50                 <li>{$err_text|escape}</li>
51             {/foreach}

```

```

54
55     <label for="surname_input">{translate key="Last name"}:</label>
56     <div class="shaded_inputwrap">
- 57         <input type="text" name="surname" id="surname_input" value="{$data.surname|escape}" size="30" c
    lass="{if $data_error.surname} error{/if}">
+ 57         <input type="text" name="surname" id="surname_input" value="{$data.surname|escape}" size="30" c
    lass="{if $data_error.surname} error{/if}" {if $data_error.surname}aria-invalid="true" aria-describedby="error_surname"{/if} autocomplet
    e="family-name">
58     </div>

```

```

59         {if $data_error.surname}
- 60         <ul class="input_error">
+ 60         <ul class="input_error error" id="error_surname">
61             {foreach from=$data_error.surname item=err_text}
62             <li>{$err_text|escape}</li>
63             {/foreach}

```

```

67         <label for="newsletter_input">{translate key="Newsletter"}:</label>
68         <div class="shaded_inputwrap">
69             <span class="checkbox-wrap">
- 70                 <input type="checkbox" name="newsletter" id="newsletter_input" value="1" {if 1 == $data.new
sletter} checked{/if}>
+ 70                 <input type="checkbox" name="newsletter" id="newsletter_input" value="1" {if 1 == $data.new
sletter} checked{/if} {if $data_error.newsletter}aria-invalid="true" aria-describedby="error_newsletter"{/if}>
71                 <label for="newsletter_input"></label>
72             </span>
73             <label for="newsletter_input">{translate key='I voluntarily agree to receive information about
new products and promotions'}</label>
74         </div>
75
76         {if $data_error.newsletter}
- 77         <ul class="input_error">
+ 77         <ul class="input_error" id="error_newsletter">
78             {foreach from=$data_error.newsletter item=err_text}
79             <li>{$err_text|escape}</li>
80             {/foreach}

```

```

98         {/if}
99
100         {if $field->field->type == constant('Logic_AdditionalField::TYPE_HIDDEN')}}
- 101         {additionalField field=$field name=$name value=$data.$name|escape}
+ 101         {additionalField field=$field name=$name value=$data.$name|escape error=$additional
_error.$name}
102         {elseif $field->field->type == constant('Logic_AdditionalField::TYPE_INFO')}}
103         <div class="input_info">
104             {$field->translation->description}

```

```

117         </span>
118         {if $field->field->type == constant('Logic_AdditionalField::TYPE_CHECKBOX')}}
119         <span class="checkbox-wrap">
- 120         {additionalField field=$field name=$name value=$data.$name editable=tru
e}
+ 120         {additionalField field=$field name=$name value=$data.$name editable=tru
e error=$additional_error.$name}
121         <label for="{ $name|escape}"></label>
122         </span>
123         <label for="{ $name|escape}">{$field->translation->description}</label>
124         {elseif $field->field->type == constant('Logic_AdditionalField::TYPE_SELECT')}}

```

```

- 125 {additionalField field=$field name=$name value=$data.$name|escape editable=
true}
+ 125 {additionalField field=$field name=$name value=$data.$name|escape editable=
true error=$additional_error.$name}
126 {else}
127 <span class="shaded_inputwrap{if $additional_error.$name} error{/if}">
- 128 {additionalField field=$field name=$name value=$data.$name|escape edita
ble=true size=25}
+ 128 {additionalField field=$field name=$name value=$data.$name|escape edita
ble=true size=25 error=$additional_error.$name}
129 </span>
130 {/if}
131 </div>

```

```

134
135 {if $additional_error.$name}
136 <div class="error">
- 137 {formErrors errors=$additional_error.$name class="input_error"}
+ 137 {formErrors errors=$additional_error.$name class="input_error" name=$name}
138 </div>
139 {/if}
140 </foreach>

```

scripts/panel/password.tpl

```

28 <em class="color">*</em> {translate key="Current password"}:
29 </label>
30 <div class="shaded_inputwrap{if $data_error.pass} error{/if}">
- 31 <input type="password" name="pass" id="pass_input" value="" size="30" />
+ 31 <input type="password" name="pass" id="pass_input" value="" size="30" {if $data_error.pass}aria
-invalid="true" aria-describedby="error_pass"{/if} aria-required="true" />
32 </div>
33 {if $data_error.pass}
- 34 <ul class="input_error">
+ 34 <ul class="input_error error" id="error_pass">
35 {foreach from=$data_error.pass item=err_text}
36 <li>{$err_text|escape}</li>
37 {/foreach}

```

```

40
41 <label for="pass1_input"><em class="color">*</em> {translate key="New password"}:</label>
42 <div class="shaded_inputwrap{if $data_error.pass1} error{/if}">
- 43 <input type="password" name="pass1" id="pass1_input" value="" size="30" />
+ 43 <input type="password" name="pass1" id="pass1_input" value="" size="30" {if $data_error.pass1}a
ria-invalid="true" aria-describedby="error_pass1"{/if} aria-required="true" />
44 </div>
45 {if $data_error.pass1}
- 46 <ul class="input_error">

```

```

+ 46      <ul class="input_error error" id="error_pass1">
47          {foreach from=$data_error.pass1 item=err_text}
48              <li>{$err_text|escape}</li>
49          {/foreach}

```

```

52
53      <label for="pass2_input"><em class="color">*</em> {translate key="Repeat password"}:</label>
54      <div class="shaded_inputwrap{if $data_error.pass2} error{/if}">
- 55          <input type="password" name="pass2" id="pass2_input" value="" size="30" />
+ 55          <input type="password" name="pass2" id="pass2_input" value="" size="30" {if $data_error.pass2}a
ria-invalid="true" aria-describedby="error_pass2"{/if} aria-required="true" />
56      </div>
57      {if $data_error.pass2}
- 58          <ul class="input_error">
+ 58          <ul class="input_error error" id="error_pass2">
59              {foreach from=$data_error.pass2 item=err_text}
60                  <li>{$err_text|escape}</li>
61              {/foreach}

```

Pliki .css

Pliki .less

styles/_panel.less

```

119 .check-label em {
120     vertical-align: top;
121 }
+ 122
+ 123 div.input a {
+ 124     text-decoration: underline;
+ 125 }
126 }

```

Pliki .js